



Fuel Pressure Bolt Kit Part # 1093076

Kit Contents

- 1 - LC Fuel Pressure Bolt
- 2 - Copper Washers

When installing please make sure to remove OEM crush washer before installing the newly supplied crush washers. The bolt will need to be secured by a wrench when installing any components, Otherwise damage may occur on the fuel rail bolt if it is not properly supported when additional parts are installed. Fuel Pressure bolt should be torqued to no more than 22ft lbs. Check and inspect for any leaks.

**Please contact our Technical Department
with questions at 928-855-6341**




Fuel Pressure Bolt Kit Part # 1093076

Kit Contents

- 1 - LC Fuel Pressure Bolt
- 2 - Copper Washers

When installing please make sure to remove OEM crush washer before installing the newly supplied crush washers. The bolt will need to be secured by a wrench when installing any components, Otherwise damage may occur on the fuel rail bolt if it is not properly supported when additional parts are installed. Fuel Pressure bolt should be torqued to no more than 22ft lbs. Check and inspect for any leaks.

**Please contact our Technical Department
with questions at 928-855-6341**



Fuel Pressure Bolt Kit Part # 1093076

Kit Contents

- 1 - LC Fuel Pressure Bolt
- 2 - Copper Washers

When installing please make sure to remove OEM crush washer before installing the newly supplied crush washers. The bolt will need to be secured by a wrench when installing any components, Otherwise damage may occur on the fuel rail bolt if it is not properly supported when additional parts are installed. Fuel Pressure bolt should be torqued to no more than 22ft lbs. Check and inspect for any leaks.

**Please contact our Technical Department
with questions at 928-855-6341**



Fuel Pressure Bolt Kit Part # 1093076

Kit Contents

- 1 - LC Fuel Pressure Bolt
- 2 - Copper Washers

When installing please make sure to remove OEM crush washer before installing the newly supplied crush washers. The bolt will need to be secured by a wrench when installing any components, Otherwise damage may occur on the fuel rail bolt if it is not properly supported when additional parts are installed. Fuel Pressure bolt should be torqued to no more than 22ft lbs. Check and inspect for any leaks.

**Please contact our Technical Department
with questions at 928-855-6341**